Tilt & Turn Windows	Compa	Company name:				Page:		Date:					System type		Sculptured			Chamfe	ered	PURF
Liniar 70mm system							d delive	n dato:					Bead type		e 28mm sculptured		28mm chamfere		0mm Ilptured	TUNI
	Compa	шу ро	sicode.			nequeste	eu uelivei	y date.					Со	lour	- Countries	<u>. </u>				UPVC Windows & Doo
Order Contact name:						Glazing			zing	Glazed			Unglazed							
	Conto										Energy rating		ting	A+ /		A		T: 023 8069 6300 E: sales@purewindows.co.uk		
Quote	r reiet	phone:	ľ	Our order number:						Secured by Design		sign	Yes			No		<u></u>		
			Width				/in	cluding	add-on)	Handle	. +./	200	Star	ndard		т	ilt safe	N	lotes / Sı	pecial requirements
			Height				(111)		uding cill)				Jiai	iuaiu		<u>'</u>	III Sale			•
			Mullion centre						600mm)				10mm 2	20mm	50mm			oupler		
			Transom drop						400mm)	Side(s) req			Тор	Bot		'∣ 2 Left	.5 Ri	20 ght		
			Large outer frame	Тор	Б	Bottom	Left		Right	Glass			Anneale		Toughen		Lamina			
			Cill type	85mm		1			1	Glass appear	_		Clear		atterned		Lamin	atou		
			Drainage	Conce			ace		one	Spacer bar				inium			adae en	acer		
OCATION	Q	TY	Sash drip bar	Conce	Yes	10		No	One	Spacer bar c			Aluli	IIIIIIIIII		vaiiii	euge sp	acei		
			Sasii diip bai		162			NO		Spacer bar c	OIC	oui								
			Width				(in	(including ad		on) Handle		ре	Standard			Tilt sa		N	lotes / S _l	pecial requirements
			Height					(including cill)		Handle c	olour									
		Mullion centre			(if not 600mr					Add-on siz		ze	ze 10mm 20m				oupler 20			
			Transom drop	Transom drop				(if not 400mm)		Side(s) requ		ired To	Тор	Bott	ttom Left		Ri	ght		
		-	Large outer frame	Тор	Е	Bottom	Lef	t Right		Glass	s type	ре			Toughened Lamin		Laminated	ated		
			Cill type	85mm	150mm	165mm	180mm	225mm	nm None	Glass appeara	rance									
OCATION	0	QTY	Drainage	Concealed		Fa	ace	N	one	Spacer bar ty		ре	Aluminium		m Warm edge space		acer			
COATION		•	Sash drip bar	Yes				No		Spacer bar co		our								
			Width				/in	al I dia a	odd oo	Handle			Ctor	dord			ilt oofo	N	lotes / Si	pecial requirements
							(111)	(including add-oi					Standar		<u> </u>		ilt safe		-	
			Height		<u> </u>			`		Handle co			40,000	20	50	Cou	ıpler C	oupler		
			Mullion centre		<u> </u>				600mm)					20mm		2	.5	20		
			Transom drop					`	400mm)	Side(s) req			Тор		tom	Left		ght		
			Large outer frame	Тор		Bottom	Left		Right	Glass			Anneale	_	Toughen		Lamina	ated		
			,,	85mm						Glass appear			Clear		atterned					
OCATION	Q	QTY	Drainage			Fa	ace		one	Spacer bar			Aluminium		n Warm edge		edge sp	acer		
	1	I	Sash drip bar				1	No		Spacer bar c	olo	MIL								

declaration.